shindaiwa®

Operator's Manual RS600 Broadcast Spreader

Specifications, descriptions and illustrative material in this literature are as accurate as known at the time of publication, but are subject to change without notice. Illustrations may include optional equipment and accessories, and may not include all standard equipment.



Read and understand all provided literature. Literature contains specifications and information for safety, operation, maintenance, storage, and assembly specific to this product. Scan QR codes for more information.



For additional literature, including safety manuals where applicable, or questions regarding terms used in this manual, visit:

https://www.echo-usa.com/manuals

OR






https://www.shindaiwa-usa.com/manuals

SERVICING INFORMATION

Parts and Serial Number

Genuine SHINDAIWA Parts and Assemblies for your SHINDAIWA products are available only from an Authorized SHINDAIWA Dealer. When you do need to buy parts always have the Model Number and Serial Number of the unit with you. For future reference, write them in the space provided below.



Model No. ______ Serial No. _____



Service

Service of this product during the warranty period must be performed by an Authorized SHINDAIWA Service Dealer. For the name and address of the Authorized SHINDAIWA Service Dealer nearest you, ask your retailer or call: 1-877-986-7783. Dealer information is also available on WWW.SHINDAIWA-USA.COM. When presenting your unit for Warranty service/repairs, proof of purchase is required.

Consumer Product Support

If you require assistance or have questions concerning the application, operation or maintenance of this product you may call the SHINDAIWA Consumer Product Support Department at 1-877-986-7783 from 8:00 am to 5:00 pm (Central Standard Time) Monday through Friday. Before calling, please know the model and serial number of your unit.

Product Registration

To ensure trouble free warranty coverage it is important that you register your SHINDAIWA equipment on-line at WWW.SHINDAIWA-USA.COM or by filling out the product registration sheet included in this manual. Registering your product confirms your warranty coverage and provides a direct link between you and ECHO if we find it necessary to contact you.

Additional Literature

In addition to finding information online, information is available from your Authorized Shindaiwa Service Dealer, or by contacting ECHO Incorporated, 400 Oakwood Road, Lake Zurich, IL 60047, 1-800-432-ECHO (3246).

SAFETY

Safety Information



Carefully read these instructions before use. Improper use or failure to follow instructions can result in product failure or injuries. For safe use of this product you must read and follow all instructions before using.



Cancer and Reproductive Harm www.P65Warnings.ca.gov




- Do not allow anyone to operate the broadcast spreader without proper instructions.
- Do not permit children to operate the broadcast spreader.
- Wear all personal protective equipment recommended by chemical manufacturer.
- Read and follow the chemical label instructions and warnings for handling and applying the chemicals you plan to spread – application settings provided are only a guideline.



DESCRIPTION

Locate the safety decal(s) on your unit. Make sure the decal(s) is legible and that you understand and follow the instructions on it. If a decal cannot be read, a new one can be ordered from your dealer. The safety decal is for example only. Your label may appear slightly different.



- 1 Top Handle Bracket
- 2 Bottom Handle Bracket
- 3 Actuator Handle
- 4 Hopper
- 5 Handle Assembly Wing Nut
- 6 Side Deflector
- 7 Wheels
- 8 Gate Adjuster
- 9 Gear Case

X7507840102

CONTENTS

The product you purchased has been partially factory pre-assembled for your convenience. Due to packaging restrictions, some assembly may be necessary.

After opening the carton, check for damage. Immediately notify your retailer or Dealer of damaged or missing parts. Use the contents list to check for missing parts.


shindaiwa"-

- 1 Broadcast Spreader Asembly
- 2 Carriage Bolts
- 2 Wing Nuts
- 1 Quick Start Guide




Install Handle Brackets

 Align holes in top handle bracket (A) with holes in bottom handle bracket (B).




RS600

- Secure handle brackets with wing nuts (C) and carriage bolts (D) on each side.
- Note: Attach each side loosely before tightening brackets securely.



NOTICE

Assure control cable is routed behind handle brackets.



Check Tire Pressure



Tires should be inflated to 15 psi. Assure tire pressure does not exceed 30 psi.

OPERATION

Application Instructions



TIP HAZARD. Unit can tip on uneven ground. Always fill hopper on flat ground, and keep bystanders away. Otherwise personal injury can result.

1. Fill Hopper

> Release actuator handle (A) to close gate. Fill hopper.

- Note: Fill hopper in an area that won't be damaged by spilled product.
- 2. Set Gate Adjustment

Push gate adjuster (B) down and move to best application setting (see chart below). Pull adjuster upward to lock in place.


Note: Gate adjustment settings should only be used as a general guideline for application. Refer to instructions on material

you are spreading for most accurate application setting requirements.

Application 3.


> A. Lower edge guard (C) and make perimeter pass to protect non-lawn areas. Pull actuator handle to open gate while spreading.

B. Raise edge guard. Make parallel internal passes to ensure even coverage.






X7507840102 © 7/21 ECHO Incorporated



Setting comparison chart / Cuadro comparativo / Régler selon la charte de comparaison																			
Shindaiwa	2	2.5	3	3	3.5	4	4.5	5	5.5	6	7	8	9	10	11	12	13	14	15
Scotts	2	2.5	3	3.25	3.5	4	4.75	5	5.5	6	7	8	9	10	11	12	13	14	15
Vigoro	2	2.5	3	3.25	3.5	4	4.75	5	5.5	6	7	8	9	10	11	12	13	14	15
Earthway	12	13	13.5	14	14.3	14.5	15	16	17	18	20	21	22	23	24	25	26	27	28

Setting by granular size / Ajuste por tamaño granular / Régler selon la taille des granules								
Setting Ajuste	2 - 2.5 Pesticide Pesticidas	3 - 3.5 Weed Control Control de hierba Contrôle des mauvais	4 - 5.5 Fertilizer Fertilizante Fertilisation	6 - 8 Overseeding Resiembra Sursemer	9 - 15 New lawn Nuevo césped Pelouses neuves			
Réglage		Controle des mauvais herbes	Fertilisation	Sursemer	Pelouses neuves			



MAINTENANCE


Clean Spreader



Avoid spraying gear case directly, and do not use a pressure washer on spreader.

shindaiwa

1. Wash spreader with a garden hose after each use.



Check Tire Pressure




shindaiwa[®]

Tires should be inflated to 15 psi. Assure tire pressure does not exceed 30 psi.


Replacing Control Cable

- 1. Remove Shield (A).
- 2. Turn gate (B) clockwise to relieve tension on cable.



RS600

3. Remove cable S hook (C) from gate.



 Remove upper handle bracket from lower handle bracket.

- 5. Remove bolts (D) and separate handle halves.
- 6. Install new handle half with control cable assembly.
- 7. Re assemble spreader components.


shindaiwa

SPECIFICATIONS

RS600

NOTICE

Assure control cable is routed behind handle brackets.



SPECIFICATIONS

MODEL	RS600					
Length	959 mm (37.75 in.)					
Width	584 mm23 in.) (
Height	794 mm (31.25 in.)					
Weight	10.2 kg (22.4 lb.)					
Capacity						
Weight	27.2 kg (60lb.)					
Volume	36.8 L (1.3 ft ³)					
Loading Height	584 mm (23 in.)					
Wheels and Tires						
Tire Diameter	254 mm (10in.)					
Tire Type	Pneumatic					
Recommended Pressure	103.4 kPa (15 psi)					

shindaiwa[®]

PRODUCT REGISTRATION

Thank you for choosing Shindaiwa Power Equipment

Please go to http://www.shindaiwa-usa.com to register your new product on-line. It's **FAST** and **EASY**! NOTE: your information will never be sold or misused by ECHO, Incorporated. Registering your purchase enables us to contact you in the unlikely event of a service update or product recall, and verifies your ownership for warranty consideration.

If you do not have access to the Internet, you can complete the form below and mail to:

ECHO Incorporated, Product Registration, PO Box 1139, Lake Zurich, IL 60047.



shindaiwa®

X7507840102 © 7/21 ECHO Incorporated

14

N2950001001 - N29500999999



400 Oakwood Road Lake Zurich, IL 60047 www.shindaiwa-usa.com